

PolarZone™ Heavy Duty ESI Antifreeze/Coolant

Heavy Duty and Fleet Applications

Description

PolarZone™ Heavy Duty ESI Antifreeze/Coolant is a premium quality (N)OAT (nitrited organic acid technology) antifreeze/coolant using nitrite and molybdate inhibitors, designed for use in heavy duty and fleet applications. This product can provide a service life of 965,000kms (600,000 miles) when properly maintained in accordance with engine manufactures maintenance recommendations.

This Extended Service Antifreeze/Coolant eliminates the need for Supplemental Coolant Additives (SCAs) at initial fill and provides unsurpassed corrosion protection to all standard metals and protection of non-metal cooling system components. The silicate and phosphate-free formulation minimizes the occurrence of deposits and hard water scale.

Advantages

- Fully formulated; does NOT require initial charge of SCA
- Provides maximum protection against rust and corrosion
- Does NOT contain phosphates, amines, or silicates
- Extends service intervals; cost savings

Applications

- Mixed fleet diesel and gas heavy duty engines
- Phosphate-free requirements of European OEMs
- Silicate-free requirements of Japanese OEMs

Meets or exceeds

- ASTM D6210, D3306

Suitable / Recommended for

- AS/NZS 2108.1:1997 Type A
- AS/NZS 2108:2004 Type A
- BS 6580
- BS 5117
- CATERPILLAR EC-1
- CID A-A-52624
- CID A-A-52624A
- CUMMINS 90T8-4
- CUMMINS CES 14603
- DETROIT DIESEL 7SE298
- DETROIT DIESEL 93K217
- FORD WSS-M97B51-A1
- FREIGHTLINER 48-22880
- FREIGHTLINER 48-25878
- GB 29743-2013
- GM HEAVY TRUCK
- ITE/NAVISTAR CEMS B-1
- ITE/NAVISTAR MPAPS B-1
- JIS K2234
- JOHN DEERE H24
- KENWORTH RO26-170-97
- KOMATSU
- MAN 324
- MB DBL 7700
- MACK 014GS17004
- MACK 014GS17009
- MACK SB 232-014
- MTU MTL 5048
- NEW HOLLAND WSN-M97B18-D
- PACCAR
- PACCAR CS0185
- PETERBILT 8502.002
- TMC RP 329
- TMC RP 338
- US FED A-A870-A
- VOLVO HEAVY TRUCK
- VOLVO / MACK
- VOLVO 128603
- WAUKESHA

Typical Characteristics - Nemco PolarZone™ Heavy Duty ESI Antifreeze/Coolant

Properties	Method	Performance	
		ESI Conc.	ESI 50:50
Colour	Appearance	Red	
SPG, 20°C(°F)	Internal	1.114	1.070
pH	ASTM D1287	8.0 - 9.0	8.0 - 9.0
Freeze point, °C(F)	ASTM D3321	-15(5)	-37(-34.6)
Boiling point, °C(F)	ASTM D3321	173(343)	106(223)
Glycol Content, %	ASTM D3321	≥91	≥48

These characteristics are typical of current production, variations in these characteristics may occur.

Availability and product codes

Pack size	4x4L case	20L pail	205L drum	1,000 Tote/Bulk
ESI Conc.	AEAFZ0011	AEAFZ0049	AEAFZ0073	AEAFZ0105
ESI 50:50	AEAFZ0010	AEAFZ0048	AEAFZ0072	AEAFZ0104
Availability	To order, contact us toll free 855-755-6737 or at orderdesk@nemco.ca			

Use and Storage

Coolant concentrate should be diluted prior to use. For best performance it is recommended coolant concentrate be premixed with distilled, deionized, or demineralized water. Dilution should not fall below a 40:60 (coolant/water) ratio at initial fill. Always check your vehicle manufacturer's specifications for coolant use. Coolant typically has a shelf life of 5 years under ideal storage conditions; keep packages closed while not in use, store in a cool and dry area.

Health, Safety, & Environment

GHS compliant Safety Data Sheets are available at nemco.ca under the Safety Data Sheets. For SDS in French, please contact info@nemco.ca. This material

is WHMIS 2015 classified. The SDS contains valuable information critical to the safe handling and proper use of the product. Always take used glycol to an authorized collection point. Avoid discharge into drains, soil, or water. As with any chemical, keep out of reach of children and animals.

Quality

Nemco works with respected industry suppliers for coolant additives and our ethylene glycol meets ASTM E1177. Nemco Resources Limited manufacturing facility in Winnipeg, Manitoba is proud to be certified to ISO9001. For questions regarding quality, please contact your local Technical Sales Representative.